

PVObject_=pvModule

Version=7.4.2

Flags=\$00D00043

PVObject_Commercial=pvCommercial

Comment=www.jinkosolar.com (China)

Flags=\$0041

Manufacturer=Jinko Solar Co., Ltd.

Model=JKM-620N-66HL4M-BDV

DataSource=TÜV NORD

YearBeg=2023

Width=1.134

Height=2.382

Depth=0.030

Weight=32.400

NPieces=100

PriceDate=07/12/23 18:47

Remarks, Count=5

Str_1=框架: Aluminium

Str_2=结构: 2 mm tempered

Str_3=连接: MC-4

Str_4

Str_5

End of Remarks

End of PVObject pvCommercial

Technol=mtSiMono

NCelS=66

NCelP=2

NDiode=3

SubModuleLayout=slTwinHalfCells

FrontSurface=fsARCoating

GRef=1000

TRef=25.0

PNom=620.0

PNomTolLow=0.00

PNomTolUp=3.00

BifacialityFactor=0.770

Isc=16.080

Voc=49.08

Imp=15.220

Vmp=40.74

muISC=7.00

muVocSpec=-121.2

muPmpReq=-0.279

RShunt=800

Rp_0=8980

Rp_Exp=5.50

RSerie=0.166

Gamma=1.149

muGamma=-0.0002

VMaxIEC=1500

Absorb=0.90

AREv=3.200

BREv=18.660

RDiode=0.010

```

VRevDiode=-0.70
AirMassRef=1.500
SandiaAMCorr=50.000
RelEffic800=0.12
RelEffic600=0.04
RelEffic400=-0.71
RelEffic200=-2.94

PVObject_IAM=pvIAM
  Flags=$00
  IAMMode=UserProfile
  IAMProfile=TCubicProfile
    NPtsMax=9
    NPtsEff=9
    LastCompile=$B18D
    Mode=3
    Point_1=0.0,1.00000
    Point_2=20.0,0.99800
    Point_3=50.0,0.97300
    Point_4=60.0,0.93600
    Point_5=70.0,0.84400
    Point_6=75.0,0.75300
    Point_7=80.0,0.60800
    Point_8=85.0,0.37500
    Point_9=90.0,0.00000
  End of TCubicProfile
End of PVObject pvIAM

OperPoints, list of=6 tOperPoint
  Point_1=False,1100,25.0,-0.16,0.00,0.000,0.000,0.00,664.66
  Point_2=True,1000,25.0,0.00,48.43,15.420,14.730,41.09,605.26
  Point_3=False,800,25.0,0.12,0.00,0.000,0.000,0.00,484.74
  Point_4=False,600,25.0,0.04,0.00,0.000,0.000,0.00,363.27
  Point_5=False,400,25.0,-0.71,0.00,0.000,0.000,0.00,240.36
  Point_6=False,200,25.0,-2.94,0.00,0.000,0.000,0.00,117.48
End of List OperPoints
End of PVObject pvModule

```